



LP/TLP 2844™ Desktop Printers LP/TLP 2824™ Desktop Printers TLP 3842™ Desktop Printer

Thermal, On-demand Label, Receipt and Tag Printers

**Leading the way
in versatile and
affordable
desktop printing**

These space-saving, quiet, user-friendly printers bring new levels of performance to the Zebra Desktop family. The 2844 bar code label printers are ideal for low-volume applications needing 104mm (4") labels, such as parcel shipping, whilst the smaller 2824 is perfect for retail product and shelf labelling or any other application where only a small label is wanted. And if you need high-resolution printing, the TLP 3842 is the answer.

**Superior
performance at a
small price**

These classy little printers from Zebra bring fast, professional labelling to your desk, small office, laboratory or anywhere you need to print small numbers of bar code labels, receipts and tags.

They are sturdily built with a double-walled ABS casing and offer many "big printer" features but at an extremely affordable price.

However, they are designed for easy use, so even complete beginners will find them simple to set up and operate.

**Thoughtfully
designed and
competitively priced!**



Reliability on demand™



LP/TLP 2844™
LP/TLP 2824™
TLP 3842™



LP 2824

TLP 2824

You get a lot of capabilities with these printers that you might have thought only came with bigger, more expensive ones.

- Label handling options include:
 - Liner-free platen (except TLP models)
 - Label dispenser with label-taken sensor
 - External rewind
 - Cutter
- A USB interface is standard on 3842 and 2844 and on serial 2824 printers. A USB conversion cable is available for parallel 2824 printers
- Ethernet network connection via a factory-installed Internal ZebraNet® PrintServer II is optional for the 2844, 3842 and serial 2824 printers. An external ZebraNet PrintServer II adapter that plugs into the parallel port can provide Ethernet connection for parallel 2824 printers or for printers which are not fitted with the internal option

Direct Thermal Printer

Perfect for low-volume printing needs in business and professional offices where a small (56mm) label is needed, such as:

- Retail
 - point-of-sale
 - shelf labelling
 - product marking
- Healthcare
 - specimen labelling
 - patient tracking
- Small office
 - mailing
 - file and folder labelling

Maximum Print Area

Width: 56mm (2.2")

Length:

279mm (11") (with standard memory)

558mm (22") (with optional memory)

Resolution

8 dots per mm (203dpi)

Maximum Print Speed

89mm (3.5") per second

Memory

Standard: 512KB Flash; 128KB SRAM

Optional: up to 1MB Flash; 256KB SRAM

Physical Characteristics

Width: 110mm

Depth: 215mm

Height: 173mm

Weight: 0.95kg

Media Specifications

Label and liner width:

25.4mm (1") to 60mm (2.36")

Direct Thermal and Thermal Transfer Printer

A space-saver with an extremely small footprint, the TLP 2824 with thermal transfer print capability is a very convenient solution for printing low-volume labels that may be exposed to heat or sunlight and those that will have a long life, for example:

- Retail product or shelf marking in garden centres
- Pharmaceutical labels
- Laboratory samples
- Patient records
- Asset management

Maximum Print Area

Width: 56mm (2.2")

Length:

279mm (11") (with standard memory)

558mm (22") (with optional memory)

Resolution

8 dots per mm (203dpi)

Maximum Print Speed

89mm (3.5") per second

Memory

Standard: 512KB Flash; 128KB SRAM

Optional: up to 1MB Flash; 256KB SRAM

Physical Characteristics

Width: 130mm

Depth: 235mm

Height: 178mm

Weight: 1.2kg

Media Specifications

Label and liner width:

25.4mm (1") to 60mm (2.36")

Ribbon width:

33mm (1.3") to 58mm (2.24")



LP 2844



TLP 2844



TLP 3842

Direct Thermal Printer

The LP 2844 comes with serial, parallel and USB interfaces as standard, so there is no problem connecting it into any system. It is ideal for a variety of low-volume applications such as:

- Shipping/Receiving
- Transportation/Logistics
- Warehouse shelf labelling
- Inventory control

Maximum Print Area

Width: 104mm (4.09")

Length:

279mm (11") (with standard memory)

558mm (22") (with optional memory)

Resolution

8 dots per mm (203dpi)

Maximum Print Speed

102mm (4") per second

Memory

Standard: 512KB Flash; 256KB SRAM

Optional: up to 1MB Flash; 512KB SRAM

Physical Characteristics

Width: 193mm

Depth: 216mm

Height: 168mm

Weight: 1.4kg

Media Specifications

Label and liner width:

25.4mm (1") to 108mm (4.25")

Direct Thermal and Thermal Transfer Printer

With thermal transfer print capability, the TLP 2844 is useful in applications where labels need to be more durable or when they will be exposed to heat and sunlight. Like the LP 2844, it integrates easily into a variety of applications including:

- Hospitals and Healthcare
- Retail product marking
- E-commerce postage

Maximum Print Area

Width: 104mm (4.09")

Length:

279mm (11") (with standard memory)

558mm (22") (with optional memory)

Resolution

8 dots per mm (203dpi)

Maximum Print Speed

102mm (4") per second

Memory

Standard: 512KB Flash; 256KB SRAM

Optional: up to 1MB Flash; 512KB SRAM

Physical Characteristics

Width: 198mm

Depth: 238mm

Height: 173mm

Weight: 1.6kg

Media Specifications

Label and liner width:

25.4mm (1") to 108mm (4.25")

Ribbon width:

33mm (1.3") to 110mm (4.3")

Direct Thermal and Thermal Transfer Printer

The 300dpi printhead of the TLP 3842 is ideal when high-resolution printing is needed for applications like:

- Laboratory or prescription bottle labelling
- Circuit board labels
- Small tags for jewellery

Maximum Print Area

Width: 104mm (4.09")

Length:

279mm (11") (with standard memory)

558mm (22") (with optional memory)

Resolution

12 dots per mm (300dpi)

Maximum Print Speed

51mm (2") per second

Memory

Standard: 1MB Flash; 512KB SRAM

Optional: up to 1.2MB SRAM

Physical Characteristics

Width: 198mm

Depth: 238mm

Height: 173mm

Weight: 1.6kg

Media Specifications

Label and liner width:

25.4mm (1") to 108mm (4.25")

Ribbon width:

33mm (1.3") to 110mm (4.3")

Standard Features

- Print methods: direct thermal (LP) or direct thermal/thermal transfer (TLP)
- Construction: ABS double-walled casing
- OpenACCESS™ design
- Serial, parallel and USB interfaces (not LP/TLP 2824)
- Head-up sensor
- Windows® drivers (95, 98, 2000, Me, NT® 4.0, XP)
- Windows printer utilities

Operating Characteristics

Environment

- Operating Temperature 5°C (40°F) to 40°C (104°F)
- Storage/Transport Environment -40°C (-40°F) to 60°C (140°F)
- Operating Humidity 10 to 90% non-condensing
- Storage Humidity 10 to 90% non-condensing

Electrical

- Autoranging external power supply
- Input: 100-240VAC; 50-60Hz
- Output: 20VDC; 2.5A

Media Characteristics

Labels

Max. Roll Size

- 127mm (5") O.D. on a 25mm (1") or 38mm (1.5") I.D. core

Thickness (label & liner)

- 0.08mm (0.003") to 0.18mm (0.0075")

Media Types

- Gap, notch, black mark, continuous, fan-fold and tag stock

For optimum print quality and printer performance, use Genuine Zebra supplies.

Fonts/Graphics/Symbologies

Fonts and Character Sets

- Standard Fonts: 5 bitmapped, expandable 8x
- Sets: international character sets supporting the following code pages:
- DOS: 437, 737, 850, 851, 855, 857, 860, 861, 862, 863, 865, 866, 869
- Windows: 1250, 1251, 1252, 1253, 1254, 1255, 1256, 1257
- Soft font storage in Flash memory

Options and Accessories

- Internal ZebraNet PrintServer II (for Ethernet connectivity) (not on 2824 parallel units)
- External ZebraNet PrintServer II (not on 2824 serial units)
- Expanded memory
Up to 1MB Flash
1.2MB SRAM (3842)
512KB SRAM (2844)
256KB SRAM (2824)
- Keyboard Display Unit (KDU)
(not on LP/TLP 2824 parallel units)

Programming

- ASCII EPL2 programming language (Page Mode)
- Text and bar codes printed in 0°, 90°, 180°, 270°
- Variable field support (up to 100)
- Counter support (up to 10)
- Variable field addition and subtraction
- Status reporting
- Form, font and graphics storage
- Line Mode support (LP 2824 or LP 2844)

Communication Interface Capabilities

- Serial RS232 (DB9)
- 1.2 to 38.4Kbits/second
- Flow control: hardware and software
- USB (except 2824 parallel units)
- Parallel (Centronics)
- LAN/Ethernet (requires optional ZebraNet® PrintServer II) (not on LP 2824 serial units)

Agency Approvals

- UL-CUL 1950; FCC (Class B); VCCI (Class B); C-TICK; EN 500082-1; EN 55022 (Class B)/CISPR 24; EN 55024/CISPR 24; EN 60950/IEC 950; EN 61000-3-2, 3-3

Ribbons (TLP 2844, TLP 2824 and TLP 3842 only)

Max. Roll Size

- 33mm (1.3") O.D. on a 12.7mm (0.5") I.D. core

Standard Length

- 74m (2,900") capacity; provides 1:1 media roll to ribbon ratios

Ribbon Set-up

- Ribbon wound ink-side out
Ribbon is recommended to be at least as wide as media

Graphic Features

- Line and box drawing
- PCX graphic storage

Bar Code Symbologies

- Linear Bar Codes: Code 39, Code 128 (A, B or C user selectable/Auto select), UCC/EAN-128, Code 93, Codabar, Interleaved 2 of 5, UPC-A, UPC-E, UPC-A with 2 and 5 add-on, Plessey, POSTNET, German Post, Japanese Postnet
- 2-Dimensional: PDF-417, Macro PDF-417, Maxi Code (Modes 2, 3, 4, 6), QR Code (requires Asian printer version), Aztec (optional), DATAMATRIX (optional)

For further information on these products, please visit the Zebra web site at:
www.zebra.com



Zebra Bar Code Products

European Headquarters
Zebra House, The Valley Centre
Gordon Road, High Wycombe
Buckinghamshire HP13 6EQ
United Kingdom
Tel: +44 (0)1494 472872
Fax: +44 (0)1494 450103

Regional Sales Office
Mollsfeld 1
D-40670 Meerbusch
Germany
Tel: +49 (0) 2159 6768 0
Fax: +49 (0) 2159 6768 22

Regional Sales Office
50 rue Marcel Dassault
F-92100 Boulogne-Billancourt
France
Tel: +33 (0)1 55 20 93 93
Fax: +33 (0)1 55 20 93 99

International Headquarters
333 Corporate Woods Parkway
Vernon Hills, IL 60061-3109
USA
Tel: +1 (847) 634-6700 or (800) 423-0442
Fax: +1 (847) 913-8766

Other Locations

United States: California, Florida, Rhode Island, Wisconsin
Europe: Denmark, Italy
Asia-Pacific: Australia, China, Japan, Singapore, South Korea
Middle East: Dubai



© 2003 Zebra Technologies
Europe Limited
Printed in the UK